



# LT Soldering Tip Family

- + Designed for universal applications
- + Universal SMT & THT jobs
- + A wide range of low cost tips
- + Solid copper plated with iron for maximum durability and long life



	Article	a / b (mm) / (inch)	Article	a / b (mm) / (inch)	Article	a / b (mm) / (inch)
<b>Chisel</b> 	<b>LT 1SC</b> T0054449499	0.4 mm / 0.15 mm 0.016 inch / 0.006 inch	<b>LT B</b> <b>BESTSELLER</b> T0054440599	2.4 mm / 0.8 mm 0.094 inch / 0.031 inch	<b>LT HX</b> T0054442099	0.8 mm / 0.4 mm 0.031 inch / inch
	<b>LT 1SCNW</b> T0054449799	0.3 mm / 0.1 mm 0.012 inch / 0.004 inch	<b>LT BSL</b> T0054451799	2.4 mm / 0.45 mm 0.094 inch / 0.018 inch	<b>LT K</b> <b>BESTSELLER</b> T0054443899	1.2 mm / 0.4 mm 0.047 inch / 0.016 inch
	<b>LT 4X</b> T0054442899	1.2 mm / 0.4 mm 0.047 inch / 0.016 inch	<b>LT BX</b> T0054444299	2.4 mm / 0.8 mm 0.094 inch / 0.031 inch	<b>LT L</b> T0054441499	2.0 mm / 1.0 mm 0.079 inch / 0.034 inch
	<b>LT A</b> <b>BESTSELLER</b> T0054444099	1.6 mm / 0.7 mm 0.063 inch / 0.028 inch	<b>LT C</b> T0054440799	3.2 mm / 0.8 mm 0.126 inch / 0.031 inch	<b>LT M</b> T0054442599	3.2 mm / 1.2 mm 0.126 inch / 0.047 inch
	<b>LT ALX</b> T0054444399	1.6 mm / 0.7 mm 0.063 inch / 0.028 inch	<b>LT D</b> T0054440999	4.6 mm / 0.8 mm 0.181 inch / 0.031 inch	<b>LT MX</b> T0054446999	3.2 mm / 1.2 mm 0.126 inch / 0.047 inch
	<b>LT ASL</b> T0054451699	1.6 mm / 0.45 mm 0.063 inch / 0.018 inch	<b>LT DLL</b> T0054444899	4.6 mm / 1.2 mm 0.181 inch / 0.047 inch	<b>LT MX2</b> T0054451299	3.0 mm / 1.0 mm 0.118 inch / 0.034 inch
	<b>LT AX</b> T0054442799	1.6 mm / 0.8 mm 0.063 inch / 0.031 inch	<b>LT H</b> <b>BESTSELLER</b> T0054443799	0.8 mm / 0.4 mm 0.031 inch / 0.016 inch		
<b>Conical long</b> 	<b>LT 1L</b> T0054442399	0.2 mm 0.008 inch	<b>LT O</b> T0054448199	0.8 mm 0.031 inch		
	<b>LT 1LNW</b> T0054449899	0.1 mm 0.004 inch	<b>LT S</b> T0054440699	0.4 mm 0.016 inch		
	<b>LT 1LX</b> T0054442499	0.2 mm 0.008 inch	<b>LT T</b> T0054448299	0.6 mm 0.024 inch		
<b>Round</b> 	<b>Round</b>		<b>Round tip sloped 45°</b>			
	<b>LT 1</b> T0054443599	0.25 mm 0.01 inch	<b>LT 4</b> T0054443999	1.2 mm 0.047 inch		
	<b>LT 1A</b> T0054448999	0.5 mm 0.02 inch	<b>LT BB 45</b> T0054448499	2.4 mm 0.094 inch		
	<b>LT 1S</b> <b>BESTSELLER</b> T0054443699	0.2 mm 0.008 inch	<b>LT DD 45</b> T0054447899	4.0 mm 0.157 inch		
	<b>LT 1SA</b> T0054448899	0.5 mm 0.02 inch	<b>LT DD 45</b> T0054448699	4.6 mm 0.181 inch		
	<b>LT 1SNW</b> T0054449699	0.1 mm 0.004 inch	<b>LT F</b> T0054440899	1.2 mm 0.047 inch		
	<b>LT 1X 30°</b> T0054442599	0.4 mm 0.016 inch	<b>LT 22CP</b> T0054440873	2.0 mm 0.079 inch		
	<b>LT AS</b> T0054440499	1.6 mm 0.063 inch	<b>LT 33CP</b> T0054440877	3.0 mm 0.118 inch		
	<b>LT BS</b> T0054449999	2.0 mm 0.079 inch	<b>Round sloped 60°</b>			
	<b>LT CS</b> T0054441199	3.2 mm 0.126 inch	<b>LT AA 60°</b> T0054448799	1.6 mm 0.063 inch		
<b>Measuring tip</b>	<b>LT Measuring tip</b> T0054441699	0.5 mm 0.02 inch				
	<b>Adapter</b>	<b>LT Adapter</b> T0054412199	<b>LT Screw in tip M4</b> T005444499			
<b>Gullwing</b> 	<b>LT GW1</b> T0054441099	1.4 mm 0.055 inch				
	<b>LT GW2</b> T0054451199	3.5 mm 0.138 inch				
<b>Knife</b> 	<b>LT KN</b> T0054447999	2.0 mm 0.079 inch				
	<b>LT KN5L 45°</b> T0054451999	2.0 mm 0.079 inch				

**Silver Line**

**Heat up time**  
 °C  
 -350  
 -300  
 -200  
 -100  
 -0  
**10 Sec.\***

**Component size**  
 S TO M

\*from 50°C to 350°C / 120°F to 620°F



<b>Round tip sloped 60°</b>	
<b>LT BB 60</b> T0054444499	2.4 mm 0.094 inch
<b>LT CC 60</b> T0054444599	3.2 mm 0.126 inch
<b>Round tip slim bent</b>	
<b>LT 1SLX 30°</b> T0054442699	0.4 mm 0.016 inch

# Weller®

weller-tools.com/toolselector/en  
 weller-tools.com/toolselector/us