



Directions:

Sweep floor with untreated dry mop. Dilute Restorer Cleaner 10:1 (10 parts water to 1 part concentrate). Using a clean rayon mop, apply a thin coat of mixed solution to the ESD floor finish. Saturate mop and wring out excess cleaner, so that the floor is not over saturated with moisture. Remove soiled solution. Allow floor to dry one hour before resuming traffic.

For auto scrubbers, gently scrub diluted solution with clean polishing pad. Use 1500 - 2000 RPM with a light pressure setting to prevent removal of finish.

Check resistance readings and apply a second treatment if necessary. Consult maintenance procedure for details and precise instructions.

Product# 4100-1: 4 gallons per case

Product# 4100-5: 5-gallon pail

Product# 4100-2: 54-gallon drum



4100 Staticide® Restorer Cleaner

Restores Gloss and Extends stripping cycles

ACL Staticide Restorer Cleaner is a specialized anti-static detergent for ESD floor finishes. When used correctly, the Restorer Cleaner can be a useful part of a maintenance program for extending the strip cycle of ACL Staticide Dissipative Floor Finishes by restoring gloss and revitalize the protective properties of the coating.

Neutral cleaners that are safe for most floor polishes can often harm ESD-safe finish by introducing contaminants and abrasive ingredients. The Restorer Cleaner will lift dirt and reestablish shine in problem areas that are prone to wear by heavy traffic. In addition, this unique concentrated formula contains special conductive additives that simultaneously break down electrical discharge, lower resistance, and return floors to safe specifications.

Whether used as a spot-cleaner or as a detergent for full floor maintenance, including Restorer Cleaner as part of a Staticide Dissipative Floor Finish maintenance plan can save companies money by successfully prolonging cleaning and strip cycles. Available as a concentrate, this cost-effective solution is suitable for mops, auto-scrubbers, and standard burnishing machines.

Ideal for the following applications:

- Electronic manufacturing facilities
- Maintaining ESD Floor Finishes
- Maintaining ESD Floor Tiles

FEATURES:

- ✿ Coverage: 1000 – 15000 square feet per gallon
- ✿ Dilution ratio: 10:1 (water to concentrate)
- ✿ Solids: 25%
- ✿ Less than 1% VOC
- ✿ No ammonia, phosphates, alkali, acids, or formaldehyde
- ✿ No Zinc
- ✿ RoHS compliant
- ✿ Use to help maintain 10e7 – 10e9 ohms on ACL floor finishes